
Bright Showers Grab Bar and Hand Shower System



Tools Needed for Installation:

- Slot-headed screwdriver
- electric drill
- 8/25" (8mm) drill bit
- Soft cloth



Parts included:

1 - Grab Bar with Adjustable Shower Head Holder
1 - 69" stainless steel hose
1 - Set of Mounting Hardware
(6 screws & 6 wall anchors)
1 - Hand shower

Please note that each of shower heads has been tested with water pressure at our factory for quality assurance,it is normal for water stains to appear on the surface,thank you!



⚠ WARNING

GRAB BAR MAY NOT PROVIDE DESIRED AMOUNT OF SUPPORT UNLESS THESE INSTALLATION INSTRUCTIONS ARE STRICTLY FOLLOWED.

TAKE PRECAUTION BEFORE DRILLING INTO THE WALL.
When drilling into the wall, exercise care to avoid any electrical wiring or plumbing that may be located behind the wall. Damaged electrical wiring can cause electrical shock and/or fire. Since older homes do not always fall in line with current housing codes and requirements, know where internal wall wiring is located so that no wires will interfere with your installation.

PROPER INSTALLATION IS EXTREMELY IMPORTANT. IF IN DOUBT, INSTALLATION SHOULD BE DONE BY A QUALIFIED PROFESSIONAL.

BEFORE INSTALLING GRAB BAR:

1. Check to make sure all parts are inside of the package.
2. Position the grab bar on the wall at the desired location. Make sure that the grab bar is level.
3. Mark the drilling holes on the wall.
(There are four holes on the back plate fixing just in case there is one hole that lies in between the tiles. Only three holes per side are necessary)
4. Make sure the button is facing upwards so the slider can hold the grab rail properly. If not, the holder may slide down the grab rail.

USING GRAB BAR:

1. Read, understand and follow the information in the SAFETY WARNINGS section of this instruction sheet. Premier Bath Fixtures LLC shall have no liability for any damage or injury caused by buyer installation or use of this Grab Bar.
2. Hold the Grab Bar when exiting or entering the bathtub or shower.
3. Use EXTREME caution on wet tub or floor surfaces.
4. DO NOT put your entire weight on the Grab Bar.
Grab Bar is rated for persons weighing up to 250 pounds when properly installed.
5. DO NOT stand, sit or step on Grab Bar.
DO NOT use Grab Bar as a step or platform to reach an area above the tub.
Use the bar for assistance ONLY.

CARE AND MAINTENANCE:

1. Use of mild soap and water or a non-abrasive cleaner is recommended for cleaning.
2. Periodically inspect the Grab Bar for damage or looseness.
DO NOT use it if any damage or looseness exists.
3. SAVE THESE INSTRUCTIONS FOR FUTURE REFERENCE.

START THE INSTALLATION:


1. Install the grab bar using the guide on the right.
2. Before snapping the cover flanges into place, make sure the wall grab bar is secured tightly.
3. The angle of the shower head and the height can both be adjusted. Push the large button on the right side to move the slide up and down the grab bar. You can adjust the angle of the shower head by rotating the holder bracket 360 degrees.

⚠ Reminder:

Please place the hand shower into the bigger slot of the holder bracket.




1




- Position and mark any 3 spots for the back plate fixing.

2




- Drill holes at the marked spots.

3




- Hammer the wall anchors into the holes respectively.

4




- Place the back plate over the wall anchors and screw it on securely

5




- Attach the cover over the back plate and press it to conceal the screws and to complete the fixing.

Note: One of the ends of the stainless steel hose has check valve to prevent water backflow, and the other end of the shower hose without check valve. Connect the nut with check valve to the inlet fitting, connect the other nut without check valve to the hand shower.



With Check Valve connected with water



Without Check Valve connected with hand

If you have any questions or concerns about this product, please don't hesitate to contact us. Thank you for choosing us as your Premier Bath Fixtures.
Email: customersupport@brightshowers.com